

RECEIVED
CENTRAL FAX CENTER

MAY 03 2006

IN THE SPECIFICATION

Please disregard the amendment submitted on November 21, 2005. The specification is further amended in the following. The undersigned states that no new matter is added.

1. The last paragraph on page 2 under the section of BACKGROUND OF THE INVENTION is amended in the following:

The preceding prior art further provides an ~~alternate~~ alternative structure at the center of the fan blade and the ~~alternate~~ alternative structure includes a first annular uneven surface and a second annular uneven surface. The first uneven surface ~~surround~~ surrounds the rotational shaft and the second annular uneven surface surrounds the first uneven surface next to an end of the sleeve. It is possible to prevent the oil contained in the bearing from leaking outward and provides a function of catching leaked oil by way of multiple round about paths.

2. The first paragraph on page 4 under the section of DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT is amended hereinafter:

Referring to Figs. 1 and 2, an anti-leak device for lubrication oil in a fan according to the present invention includes a fan blade wheel 1 and a fan frame 2. The fan blade wheel 1 is composed of a hub 11 and a plurality of blades 12 extending outward from the hub 11 radially. The hub 11 has ~~at the center thereof~~ a rotational shaft 111 at the center thereof and ~~at inner side thereof~~ an annular recess 113 at the inner side thereof around the shaft 111. The fan frame 2 provides a hub seat 21 with a sleeve 211 and a durable pad 212, an engaging piece 213 and a bearing 214 are received in the sleeve 211. The engaging piece

OK to enter, AP 878-DB

BEST AVAILABLE COPY**IN THE SPECIFICATION**

The specification is amended in the following and the undersigned states that no new matter is added.

1. The last paragraph on page 2 under the section of BACKGROUND OF THE INVENTION is amended in the following:

The preceding prior art further provides an ~~alternate~~— alternative structure at the center of the fan blade and the ~~alternate~~— alternative structure includes a first annular uneven surface and a second annular uneven surface. The first uneven surface surround the rotational shaft and the second annular uneven surface surrounds the first uneven surface next to an end of the sleeve. It is possible to prevent the oil contained in the bearing from leaking outward and provides a function of catching leaked oil by way of multiple round about paths.

2. The first paragraph on page 4 under the section of DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT is amended hereinafter:

Referring to Figs. 1 and 2, an anti-leak device for lubrication oil in a fan according to the present invention includes a fan blade wheel 1 and a fan frame 2. The fan blade wheel 1 is composed of a hub 11 and a plurality of blades 12 extending outward from the hub 11 radially. The hub 11 has ~~at the center thereof~~ a rotational shaft 111 at the center thereof and ~~at inner side thereof~~ an annual recess 113 at the inner side thereof around the shaft 111. The fan frame 2 provides a hub seat 21 with a sleeve 211 and a durable pad 212, an engaging

do not enter, AP 8-18-06